UNCLASSIFIED

Defense Technical Information Center Compilation Part Notice

ADP013210

TITLE: Vibration Study of Nitrogen Incorporation in InGaAsN Alloys

DISTRIBUTION: Approved for public release, distribution unlimited Availability: Hard copy only.

This paper is part of the following report:

TITLE: Nanostructures: Physics and Technology International Symposium [9th], St. Petersburg, Russia, June 18-22, 2001 Proceedings

To order the complete compilation report, use: ADA408025

The component part is provided here to allow users access to individually authored sections of proceedings, annals, symposia, etc. However, the component should be considered within the context of the overall compilation report and not as a stand-alone technical report.

The following component part numbers comprise the compilation report: ADP013147 thru ADP013308

UNCLASSIFIED

Vibrational study of nitrogen incorporation in InGaAsN alloys

A. M. Mintairov†‡, P. A. Blagnov†, J. L. Merz‡, V. M. Ustinov† and A. S. Vlasov†
† Ioffe Physico-Technical Institute, St Petersburg, Russia
‡ Dept. of Electrical Engineering, University of Notre Dame,
Notre Dame, IN 46556, USA

Abstract. We present an infra-red (IR) reflectivity and Raman study of $In_x Ga_{1-x} As_{1-y} N_y$ (x=0 and ~ 0.08 , $y \sim 0.03$) alloys grown by molecular beam epitaxy. We observed: — strong diagonal Raman components of GaAs-type phonons, indicating a local trigonal distortion of the alloy lattice induced by nitrogen ordering; — indium induced splitting of the Ga-N type vibration, indicating a formation of different local nitrogen atomic arrangements; — a sharp (halfwidth $\sim 1 \text{ cm}^{-1}$) IR mode at 360 cm⁻¹, of unknown origin.

Introduction

The InGaAsN alloys have recently attracted considerable attention as promising materials for laser diodes in the 1.3–1.5 μ m range as well as more efficient solar cells. These applications exploit the unusual electronic property — a "giant bowing", which arises from the large electronegativity and very small ion radii of the nitrogen [1, 2], together with the possibility of perfect lattice matching to GaAs substrates. Up to now little is known about the micro/nanostructure, i.e. possible atomic ordering and phase separation, of these alloys, which can dramatically alter their electronic and transport properties important for device applications. In our previous paper [3] using Raman spectra we revealed local trigonal distortion of coherently strained $GaAs_{1-x}N_x$ ($x \sim 0.02$) alloys, indicating the existence of [111] GaAs/GaN ordering. In present paper using Raman and IR vibrational spectroscopy we study of the properties of N incorporation into InGaAsN alloys lattice matched to GaAs.

1. Experiment

Coherently strained $GaAs_{1-y}N_y$ and lattice matched $In_xGa_{1-x}As_{1-y}N_y$ ($x \sim 0.08$, $y \sim 0.03$) layers with thickness $\sim 0.2~\mu m$ were grown by solid source MBE on (001) semi-insulating GaAs substrates at temperature $450^{\circ}C$. An RF-plasma source was used to generate atomic nitrogen from N2. The composition was determined by calibration growths of GaAsN and InGaAs along with x-ray diffraction. The layers have strong photoluminescence at room temperature at 1.05-1.15 eV.

We also used MOCVD grown reference samples of $In_xGa_{1-x}As$ ($x \sim 0.1$) and $GaAs_{1-y}N_y$ ($y \sim 0.03$) studied by us previously in [3].

Polarized room temperature IR spectra were taken at oblique incidence (45°) with a Bruker IFS-66V spectrometer.

The Raman spectra (RS) were measured in the backscattering geometry using a double monochromator DFS-52 and excited with a 488 nm Ar⁺-ion laser at room temperature. The xy and xx (where the $x \parallel [100]$ and $y \parallel [010]$) components of RS excited from the (001) growth plane were analyzed. According to Raman selection rules of zinc blende structure

NC.13p 239

only optical phonons with longitudinal (LO) polarization are allowed in xy configuration, while all optical modes are forbidden in the xx one.

2. Results and discussion

The results of our IR and Raman measurements are presented in Figs. 1–4. As can be seen from Fig. 1, the IR spectra of $In_{0.07}Ga_{0.93}As_{0.97}N_{0.03}$ alloys have a main intense restrahl band 270–290 cm⁻¹ due to the GaAs-type phonons, a very sharp peak A at 360 cm⁻¹, and several weak bands in the range 400–550 cm⁻¹, corresponding to second order spectra of GaAs-type. The Ga-N type phonon TO_2 also observed at 470 cm⁻¹.




Fig. 1. Polarized (s — solid, p — dashed curves) IR reflection spectra of In_{0.07}Ga_{0.93}As_{0.97}N_{0.03} alloys.

The A peak has unusually small halfwidth 1.5 cm⁻¹, which is much smaller then the typical phonon damping parameter of binary III–V compounds (~3 cm⁻¹). We observed this IR peak in all GaAsN and InGaAsN layers grown by MBE, but it was absent in the IR spectra of the MOCVD grown GaAsN layers. On the other hand, our Raman measurements did not reveal any band at 360 cm⁻¹, what makes the origin of this peak at the moment unclear.




Fig. 2. s-polarized IR reflection spectra of $GaAs_{1-y}N_y$, $In_xGa_{1-x}As_{1-y}N_y$ alloys and GaAs substrate in 400–600 cm⁻¹ frequency range.




Fig. 3. xy (left) and xx (right) Raman components of Ga-N type mode of $In_{0.07}Ga_{0.93}As_{0.02}N_{0.98}$ and $GaAs_{0.965}N_{0.035}$.

In the IR spectra we observed the GaN-type vibration (TO₂) in both InGaAsN and GaAsN, as can be seen from Fig. 2, where we compare the spectra of three $In_xGa_{1-x}As_{1-y}N_y$ ($x \sim 0.08$, $y \sim 0.03$) and one $GaAs_{1-y}N_y$ ($y \sim 0.035$) layers with the spectra of GaAs. It can bee seen that in InGaAsN the TO₂ band is much broader. It reveals a fine structure consisting of a low — TO_{2b} and a high — TO_{2a} frequency shoulder split by ~ 15 cm⁻¹ from the central TO_2 peak. The splitting clearly indicates that there are three different local atomic arrangements of nitrogen in the lattice of InGaAsN, which is induced by the presence of indium.

In the Raman spectra the Ga-N type mode was observed only in GaAsN (see Fig. 3). As in our previous study [3] it appears in both zinc blende allowed — xy and forbidden — xx configurations, which is due to a strong local trigonal distortion of the GaAsN lattice




Fig. 4. xy (left) and xx (right) Raman components of GaAs-type modes of GaAs (1), In_{0.14}Ga_{0.86}As (2), In_{0.07}Ga_{0.93}As_{0.02}N_{0.98} (3) and GaAs_{0.965}N_{0.035} (4) alloys.

NC.13p 241

caused by the bond relaxation and ordering of GaN₃As microclusters ([111] GaN/GaAs ordering).

While we did not detect the GaN-type mode in InGaAsN we did get evidence that the GaN_3As microcluster ordering is preserved in the presence of In. This is seen in Fig. 4, where the strong enhancement (compared with GaAs and InGaAs) of the forbidden xx scattering of the GaAs-type TO_1 phonon is observed for both GaAsN and InGaAsN.

The appearance of the strong zinc blende forbidden Raman components, indicating [111] GaN/GaAs ordering, is an anomalous property of InGaAsN, which was not observed in conventional III–V alloys. The results presented show that it does not depend on the macroscopic strain due to lattice mismatch between epi layer and substrate. The driving force for the ordering can be strong local strains (bond relaxation) caused by the small nitrogen radii.

Acknowledgments

The authors wish to acknowledge the NATO Science for Piece Program (grant SFP-972484).

References

- [1] S. Sakai, Y. Ueta and Y. Terauchi, Jpn. J. Appl. Phys. 32, p. 4413 (1993).
- [2] S.-H. Wei and A. Zunger, Phys. Rev. Lett. 76, 664 (1996).
- [3] A. M. Mintairov, P. A. Blagnov, V. G. Melehin, N. N. Faleev, J. L. Merz, Y. Qiu, S. A. Nikishin and H. Temkin, *Phys. Rev. B* 56, 15836 (1997).